

## SAFETY DATA SHEET

### MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032

Preparation Date: 12.12.2025  
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

#### 1. Description of the substance/mixture and of the company/distributor;

##### 1.1. The identity of the substance/mixture;

Product form : Mixture  
Trade Name : Mold Protectant Spray  
EC Number : Unknown  
CAS Number : Unknown

##### 1.2. Identified uses of the substance or mixture and uses advised against;

Wooden profiles , MDF, rubber, particleboard, plastic and tires, and for repairing and fixing wooden parts.

##### 1.3. Information about the supplier of the Safety Data Sheet;

Manufacturer : MAXRAY Kimya San. ve Tic. Ltd. Şti  
Address : Mimar Sinan Mah. Üsküdar Cad. YEDPA No:1 Cad. Inner door No:2  
ATAŞEHİR/İSTANBUL  
Phone : +90 850 307 04 47  
Email : info@maxray.com.tr  
Contact Person : Nurullah Düzgün  
Product Code : MX-78040  
Product Type : Industrial

##### 1.4. Emergency phone number;

Emergency phone number : 114 (Poison Control Center / For local calls only.)

#### 2. Hazard identification;

##### 2.1. Classification of substances and mixtures;

##### Classification of the mixture in accordance with Regulation (EC) No 1272/2008

BHOT Single Mrz, Hazard Category 3 (Dizziness)	H336
Aspiration Toxicity, Hazard Category 1	H304
Aquatic chronic, Pest Category 2	H411
Skin irritation, Hazard Category 2	H315
Skin Sensitivity, Hazard Category	H317
Highly flammable aerosol	H222
Pressure Box	H229
Reproductive Sist . Tok. 2	H361

The full text of the H statements; see Section 16.

##### 2.2. Label elements;

##### Classification of the mixture in accordance with Regulation (EC) No 1272/2008

Hazard Label (SEA) :       
GHS02 GHS07 GHS08 GHS04 GHS09

Warning word (SEA) : Danger

## SAFETY DATA SHEET

### MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032

Preparation Date: 12.12.2025  
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

#### Hazard Statements (SEA)

- H222 Highly flammable aerosol.
- H229 Pressure canister: may explode if heated.
- H304 - Fatal if inhaled or swallowed.
- H336 - May cause drowsiness or dizziness.
- H361 - Suspected of causing harm to the unborn child or impairing fertility.
- H315 - Causes skin irritation.
- H317 - Causes allergic skin reactions.
- H411 - Long-lasting toxic effect in aquatic environment.

#### Precautionary Statements (SEA)

- P102 - Keep out of reach of children.
- P210 - Keep away from heat/sparks/flames/hot surfaces. - No smoking.
- P362: Remove soiled clothing and wash it before reusing.
- P251: Pressure vessel: Do not puncture or burn, even after use.
- P410+P403: Protect from sunlight. Store in a well-ventilated area.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P260: Do not inhale dust/fumes/gas/mist/vapor/spray.
- P304+P340: IF INHALED: Remove the affected person to fresh air and keep them in a comfortable position to facilitate breathing.
- P403+P233: Store in a well-ventilated area. Keep the container tightly closed.
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122F.
- P501: Dispose of contents/container in accordance with local/regional/national/international regulations (as specified). Indicate whether this applies to the contents, container, or both, as instructed by the manufacturer/supplier or competent authority.

#### 2.3. Other damages;

PBT or vPvB substances.

### 3. Information about its composition/ingredients;

#### 3.1. Items;

Not applicable.

#### 3.2. Mixtures

Name of the Substance	CAS Number	EC Number	%	Classification in accordance with the "Regulation on the Classification, Labelling and Packaging of Substances and Mixtures" (SEA), published in the Official Gazette dated December 11, 2013, and numbered 28848 ( mükerrer).	Pictograms
Hydrocarbons , C6, n- alkanes , iso-alkanes ,	---	925-292-5	40- 60	Flame. Liquid 2, H225 Urm . Sis. Tok.2,H361	GHS02 GHS07 GHS08 GHS09

## SAFETY DATA SHEET

### MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032

Preparation Date: 12.12.2025  
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

cyclics , nhexane rich				Asp.Tok . 1, H304 STOT Tech. MRZ.2, H373 Volume Tah . 2, H315 BHOT TEK MRZ.3,H336 Aquatic Chronic 2,H411	Dangerous
Harmful Components	--	--	5- 15	Flame. Liquid .3 , H226 Asp.Tok.1 , H304 Volume Thrş 2, H315 Skin Sensitivity 1, H317 EUH066	GHS02 GHS08 GHS07 Dangerous
Petroleum gases, liquefied	68476-85-7	270-704-2	15- 30	Flame. Gas 1, H220	GHS02 DANGER

For the full text of the H statements, see Section 16.

Additional Information < 0.1% Benzol (benzene)

#### 4. First aid measures;

##### 4.1. Explanation of first aid measures;

Inhalation	Remove the patient from the danger zone, keep them warm, and allow them to rest. Seek medical assistance. Use a ventilator if breathing is difficult.
Contact with skin	Remove all contaminated clothing and footwear. Wash thoroughly with plenty of soap and water.
Eye contact	Immediately lift your eyelids and rinse thoroughly with plenty of water. If discomfort persists, seek medical attention.
If swallowed	Do not induce vomiting. Consult your doctor immediately.

##### 4.2. Significant symptoms and effects, both immediate and delayed.

Effects and Symptoms

Inhalation	: May cause dizziness and lightheadedness. High concentrations may cause eye irritation and nausea. Symptom: Restlessness.
Skin contact	: Skin irritation , erythema , edema, and pruritus .
Eye contact	: May cause conjunctivitis .
If swallowed	: It can damage organs involved in nutrition, such as the esophagus. It can cause nausea, vomiting, and diarrhea. In case of vomiting, respiratory tract damage and pneumonopathy may occur.

##### 4.3. The first signs that require medical intervention and specialized treatment.

Treat symptomatically .

#### 5. Firefighting measures;

##### 5.1. Fire extinguishers

Fire Extinguishing Vehicles

Suitable for	: Use carbon dioxide, dry chemicals, and foam.
Not suitable	: Do not use a water jet.

## SAFETY DATA SHEET

### MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032

Preparation Date: 12.12.2025  
Revision Date/Number: 00/00

*According to Commission Regulation (EU) 2020/878 as amended*

#### 5.2. Specific hazards arising from the substance or mixture.

Specific exposure hazards : Highly flammable vapors are heavier than air. They can reach ignition sources. The vapor can form an explosive mixture with air.

Hazardous thermal decomposition products : harmful substances such as carbon monoxide, carbon dioxide, HCl, phosgene, and chlorine can be released.

#### 5.3. Recommendations for firefighting teams

Special for firefighters. Use appropriate respiratory protection equipment in case of inadequate ventilation. Cool the outside of containers with water.

#### 6. Measures to prevent accidental release;

##### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : If spillage occurs in an enclosed area, clean and ventilate the area.

Personnel involved in application should wear hydrocarbon protective gloves, goggles, boots, and clothing. Adequate ventilation must be ensured.

##### 6.2. Environmental measures

Environmental precautions : Prevent spills and spread. Prevent spills from entering sewers, drainpipes, basements, and enclosed spaces. Report spills to authorities if they contaminate streams or sewers.

Other information : Unknown.

##### 6.3. Methods and materials for preservation and cleaning.

Cleaning methods : Absorb the spills with an inert material (e.g., dry sand, soil, diatomaceous earth, sawdust ) and place them in chemical waste containers. Clean the floor with water.

##### 6.4. References to other sections

References to other sections : See also section 8.

#### 7. Handling and storage;

##### 7.1. Precautions for safe handling

Precautions for safe handling : Handle in well-ventilated areas . Prevent vapor formation. Do not inhale vapors. Avoid contact with skin and mucous membranes. Handle away from sources of flame . Prevent static electricity buildup. Do not smoke. Do not use compressed oxygen or air during transfer and discharge. Have equipment to prevent the spread of fire. Use only cold and gas-free reservoirs. Pay attention to grounding. Discharge slowly, especially at the beginning of the process . Do not spray at high pressures (>3 bar).

##### 7.2. Conditions for secure storage, including disputes.

Storage conditions : Static electricity buildup must be prevented. Store away from flames and heat sources. Containers and devices must be grounded. Keep containers closed when not in use. Store in a dry, cool, and dark place.

Recommended packaging : Store only in the packaging in which it was supplied.

# SAFETY DATA SHEET

## MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032Preparation Date: 12.12.2025  
Revision Date/Number: 00/00*According to Commission Regulation (EU) 2020/878 as amended*

### 7.3. Specific end uses

Usage : Use only as directed.

### 8. Exposure control/personal protection;

#### 8.1. Control parameters

Hydrocarbons , C6, n- alkanes , iso-alkanes , cyclics , n- hexane rich

Observed Effects	Exposure	DNEL	Type of Toxicity
Worker damage limits			
Inhalation - Systemic Effects	Prolonged exposure	93 mg/ m <sup>3</sup>	
Dermal -Systemic Effects	Prolonged exposure	13 mg/kg / day	Neuro toxicity
Damage limits for the general population.			
Inhalation - Systemic Effects	Prolonged exposure	20 mg/ m <sup>3</sup>	Acute toxicity
Dermal -Systemic Effects	Prolonged exposure	7 mg/kg / day	Acute toxicity
Oral-Systemic Effects	Prolonged exposure	6 mg/kg / day	Acute toxicity

N,N- dimethyl -p -toluidine

Observed Effects	Exposure	DNEL	Type of Toxicity
Worker damage limits			
Inhalation - Systemic Effects	Prolonged exposure	1,224 mg/ m <sup>3</sup>	Reproductive
		73,436 mg/m <sup>3</sup> · NOAEL	
Dermal -Systemic Effects	Prolonged exposure	0.694 mg/kg / day	Reproductive
		41.65 mg/kg / day (NOAEL)	
<b>Observed Effects</b> <b>Exposure</b> <b>DNEL</b> <b>Type of Toxicity</b>			
Eye-Local Effects	No damage was reported.		
Damage limits for the general population.			
Inhalation - Systemic Effects	Prolonged exposure	0.302 mg/ m <sup>3</sup>	Reproductive
		36,217 mg/m <sup>3</sup> · NOAEL	
Dermal -Systemic Effects	Prolonged exposure	0.347 mg/kg / day	Reproductive
		41.65 mg/kg / day (NOAEL)	
Oral-Systemic Effects	Prolonged exposure	0.174 mg/kg / day	Reproductive
		20,825 mg/kg / day (NOAEL)	
Eye-Local Effects	No damage was reported.		

Petroleum gases, liquefied (&lt;0.1% 1,3- butadiene )

Observed Effects	Exposure	DNEL	Type of Toxicity
Worker damage limits			
Inhalation - Systemic Effects	Prolonged exposure	2.21 mg/ m <sup>3</sup>	Carcinogenicity
Dermal -Systemic Effects	Prolonged exposure	23.4 mg/kg / day	Carcinogenicity
Damage limits for the general population.			

## SAFETY DATA SHEET

### MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032

Preparation Date: 12.12.2025  
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

Inhalation - Systemic Effects	Prolonged exposure	0.066 mg/ m <sup>3</sup>	Carcinogenicity
-------------------------------	--------------------	--------------------------	-----------------

#### 8.2. Exposure controls

- Engineering measures : Ensure adequate general and local ventilation. The ventilation system should be regularly maintained and inspected. Observe the exposure limits of the product or content.
- Hygiene precautions : General hygiene rules regarding the use of chemical substances should be applied. Wash your hands during breaks and after work. Keep away from food, drinks, and meals. Remove contaminated clothing and protective equipment before entering eating areas.
- Personal protective equipment : The effectiveness of personal protective equipment depends, among other factors, on temperature and ventilation. Professional advice should be sought depending on the specific situation.
- Body protection : Wear protective clothing, work overalls or suit and similar footwear conforming to EN 365/367, specifically standard 345. Suitable material: nitrile . Insulation time: impermeable.
- Respiratory protection : In well-ventilated areas, no special equipment is required. In poorly ventilated areas, use artificial respiration.
- Hand protection : Wear gloves conforming to EN 374 standard . Suitable material: nitrile . ± 0.5 mm penetration time: impermeable. Replace gloves as needed.
- Eye protection : Use tightly fitting, chemical-protective goggles or a face shield. If there is a risk of inhalation, use a full-face gas mask.

#### 9. Physical and chemical properties;

##### 9.1. Basic physical and chemical properties

- Physical Appearance : Liquid
- Color : Yellow
- Scent : Characteristic
- Odor threshold : Unknown
- Flash Point (°C) ( min ) : ≤0
- Boiling Point (°C) ( min ) : Unknown
- Density (g/ cm<sup>3</sup> ) : 0.70 -0.90
- pH : Unknown
- Viscosity ( cSt ) : Unknown
- Flash Point : Unknown
- Vapor Pressure : Unknown
- Vapor density : Unknown
- Solubility Feature : Not Soluble
- Refractive Index : 25-31

##### 9.2. Other information

No further information available.

#### 10. Stability and reactivity;

# SAFETY DATA SHEET

## MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
 GBF Form No: M-00032

Preparation Date: 12.12.2025  
 Revision Date/Number: 00/00

*According to Commission Regulation (EU) 2020/878 as amended*

**10.1. Reaction**

Reactivity: There are no known harmful reactive effects .

**10.2. Chemical stability**

Stability : It is stable under normal conditions.

**10.3. Possibility of harmful reactions**

Reactivity : The likelihood of a reaction occurring is high in the presence of oxidizing agents.

**10.4. Situations to avoid**

Conditions to avoid : Avoid sources of flame such as heat and sparks. Containers may explode or burn fiercely due to excessive pressure when heated . Static electricity buildup must be prevented.

**10.5. Substances to avoid**

Materials to avoid: Oxidizing agents.

**10.6. Harmful decomposition products,**

Hazardous decomposition products : Do not decompose if stored and used under appropriate conditions . Products that decompose thermally or are compressed may include: harmful gases and vapors.

**11. Toxicological information;**

**11.1. Information about toxic effects**

Article	Toxicity Type	Toxicity Zone	Test Animal	Conclusion
Hydrocarbons , C6, n- alkanes , iso-alkanes , cyclics , n- hexane rich	Acute	Oral	Rat/Male	LD 50: >25 ml/kg
		Breathing	Rat/Male	LC 50: 259354 mg/ m <sup>3</sup>
		Dermal	Rabbit/Male	LD 50: >5 ml/ kg
	Irritation	Dermal	Rabbit	None
		Eyelash	Rabbit	None
	Sensibility	Dermal	Mouse	None
	Repeat Dose	Oral	Rat/Male	LOAEL; 37973 mg/kg NOAEL; 1135 mg/kg / day
			Inhalation/Syste- mic	Rat/Female- Male
		Genetic		Rat
	Reproductive/Dev- elopmental toxicity	Breathing	Rat	NOAEC; 3000 ppm LOAEC; 9000 ppm
Petroleum gases, liquefied (<0.1% 1,3- butadiene )	Acute	Breathing	Rat/Female- male	LC 50: 800,000 ppm EC 50: 280000 ppm
	Repeat Dose	Inhalation/Systemic	Rat/Female- Male	No harmful effects have been observed.

# SAFETY DATA SHEET

## MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032

Preparation Date: 12.12.2025  
Revision Date/Number: 00/00

*According to Commission Regulation (EU) 2020/878 as amended*

			NOAEC; 19678 mg/m <sup>3</sup>
	Genetic		None
	Reproductive	Rat/Female- Male	NOAEC: 16000 ppm
	Teratogenicity	Breathing Rat	NOAEC: 16000 ppm
	Carcinogenicity	Rat/Female- Male	NOAEC: 10000 ppm An effect was observed at 17200 mg/m <sup>3</sup>

### 12. Ecological information;

#### 12.1. Toxicity

Hydrocarbons , C6, n- alkanes , iso-alkanes , cyclics , n- hexane rich

Short-term toxicity (fish) : LL50: 13.37 mg/l (96 hours)

Long-term toxicity (fish) : NOELR: 2992 mg/l

Short-term toxicity (invertebrates) : LL50: 23.35 mg/l (48 hours)

Long-term toxicity (invertebrates) : NOELR: 5224 mg/l (21 days)

Toxicity (Algae, cyanobacteria ) : EL50: 9902 mg/l (48 hours)

Toxicity (Microorganisms) : EL50: 51.6 mg/l (48 hours)

Petroleum gases, liquefied (<0.1% 1,3- butadiene )

Short-term toxicity (fish) : LC50: 49.47 mg/l (96 hours)

Short-term toxicity (invertebrates) : LC50: 69.43 mg/l (48 hours)

Toxicity (Algae, cyanobacteria ) : EC50: 12.32 mg/l (96 hours)

Toxicity (Microorganisms) : EL50: 51.6 mg/l (48 hours)

#### 12.2. Persistence and degradability

Persistence : Biodegradable .

#### 12.3. Bioaccumulation potential

Potential for bioaccumulation : There is no known potential for bioaccumulation.

#### 12.4. Mobility in the soil

Mobility : Not applicable.

#### 12.5. Results of PBT and vPvB assessment

PBT/ vPvB values : Does not contain PBT or vPvB substances.

#### 12.6. Other negative effects

Other information : Not applicable.

### 13. Disposal information;

#### 13.1. Waste processing methods

Product residue : Recyclable container. Do not puncture or burn, even after use. Do not dispose of empty packaging with normal household waste. Containers should be recycled or reused. Product residues, including non-empty packaging, should be treated as chemical waste.

Additional warning : Unknown.

European Waste Catalogue : Dispose of hazardous waste in an official chemical waste storage facility in accordance with Directive 91/689/EEC and under a waste law pursuant to Commission Decision 2000/532/EC.

## SAFETY DATA SHEET

### MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032

Preparation Date: 12.12.2025  
Revision Date/Number: 00/00

*According to Commission Regulation (EU) 2020/878 as amended*

Local regulations : Waste disposal must comply with applicable regional, national, and local laws and regulations. Local regulations may be stricter than regional and national requirements and must be complied with.

#### 14. Transportation information;

14.1. UN Number : UN 1950

14.2. Appropriate UN shipping name

Appropriate shipping name : AEROSOLS

Proper shipping name (IMDG, IATA) : AEROSOLS

14.3. Transportation hazard class( es ) : 2 (ADR/RID/ADN/IMDG/IATA)

Classification Code : 5F (ADR/RID/ADN)



Hazard Label : 2.1

14.4. Packaging group : None

14.5. Environmental damage

Marine pollutant : NO

14.6. Special measures for the user

Unless otherwise stated, measures applicable to safe transport will be taken.

IATA Cargo Aircraft: 203

IMDG - Technical name: Aerosol

IMDG Page: F -D, SU

14.7. Public transport according to MARPOL 73/78 Annex II and IBC code.

Marpol : As per the instructions above, it is not a hazardous product.

#### 15. Knowledge of legislation;

15.1. Specific safety, health and environmental regulations for the substance or mixture.

##### National Legislation

- Turkish Ministry of Environment and Urbanization, Regulation No. 28848, dated December 11, 2013, on the Classification, Labelling and Packaging of Substances and Mixtures.
- Turkish Ministry of Environment and Urbanization, Waste Management Regulation, dated April 2, 2015, numbered 29314.
- Turkish Ministry of Labour and Social Security, Regulation No. 28733 dated August 12, 2013, on Health and Safety Measures in Work with Chemical Substances.
- Turkish Ministry of Labour and Social Security, Regulation No. 28695 dated July 2, 2013, on the Use of Personal Protective Equipment in Workplaces.
- Turkish Ministry of Labour and Social Security, Occupational Health and Safety Law No. 6331, dated June 30, 2012.

## SAFETY DATA SHEET

### MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032

Preparation Date: 12.12.2025  
Revision Date/Number: 00/00

*According to Commission Regulation (EU) 2020/878 as amended*

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### 16. Other information;

##### Abbreviations

Flammable Liquid 2 : Flammable Liquid, Hazard Category 2.  
Reproductive System Toxic, Hazard Category 2  
BHOT TEK. MRZ 3 : Specific Target Organ Toxicity - Single Exposure , Category 3  
Asp.Tok . 1 : Aspiration Toxicity , Hazard Category 1  
BHOT Tek. MRZ.2 : Specific Target Organ Toxicity - Repeated Exposure , Category 2  
Eye Irritation 2 : Eye Irritation, Hazard Category 2  
Skin Irrit. 2 : Skin Irritation, Hazard Category 2  
Cance. 2 : Carcinogenicity , Hazard Category 2  
LD50 : The dose of a substance that causes 50% (half) death in the test animal group (Median Lethal Dose)  
LC 50 : Concentration of a substance causing 50% (half) mortality in a test animal group.  
ADR : European Agreement concerning the international carriage of dangerous goods by road.  
IMDG : International Maritime Dangerous Goods  
IATA : International Air Transport Association  
ADN : European Agreement concerning the international carriage of dangerous goods by inland waterways  
RID : European Agreement concerning the international carriage of dangerous goods by rail.  
Merpel 73/78 : International Convention for the Prevention of Pollution from Ships, 1973, as amended by Protocol 1978. IBC: International Code for the Construction and Equipment of Ships Carrying Dangerous Bulk Chemicals (International Bulk Chemicals Code)  
WEL : Workplace Exposure Limit  
TWA : Workplace Exposure Limits  
STEL : Short-Term Exposure Limit  
EC No : European Community Number  
CAS : Service for Chemical Theories  
PBT : Persistent, Bioaccumulative , and Toxic Substance.  
vPvB : Very Persistent, Highly Bioaccumulative  
DNEL : Derived Effect Unobserved Time  
Va : Body weight  
Certificate Number: TÜV/11.302.03  
Certificate Expiration Date: 05.11.2030



# SAFETY DATA SHEET

## MOLD PROTECTANT SPRAY

Product Name: Mold Protectant Spray  
GBF Form No: M-00032

Preparation Date: 12.12.2025  
Revision Date/Number: 00/00

*According to Commission Regulation (EU) 2020/878 as amended*

### LEGAL NOTICE (DISCLAIMER)

The evaluations contained in the Product Safety Data Sheet have been prepared based on the information currently available to us and are published for the purpose of identifying the products in terms of health, safety, and environmental aspects. Maxray Kimya San. ve Tic. Ltd. Şti. makes no representation or warranty, either express or implied, regarding the accuracy or completeness of the data contained herein. This document should not be interpreted as a guarantee of any specific property of the product. The data and recommendations provided are applicable only to cases in which this product is sold for the specified application(s). This product should not be used for any purpose other than the stated application area without consulting Maxray Kimya San. ve Tic. Ltd. Şti.