

SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

1. Description of the substance/mixture and of the company/distributor;

1.1. The identity of the substance/mixture;

Product form : Mixture
Trade Name : Pre Filled
EC Number : Unknown
CAS Number : Unknown

1.2. Identified uses of the substance or mixture and uses advised against;

It is used in vehicles, construction machinery, household appliances, all kinds of metal and wooden surfaces, and for hobby purposes.

1.3. Information about the supplier of the Safety Data Sheet;

Manufacturer : MAXRAY Kimya San. ve Tic. Ltd. Şti.
Address : Mimar Sinan Mah. Üsküdar Cad. YEDPA No:1 Cad. Inner door No:2
ATAŞEHİR/İSTANBUL
Phone : +90 850 307 04 47
Email : info@maxray.com.tr
Contact Person : Nurullah Düzgün
Product Code : MX-77876
Product Type : Spray Paint

1.4. Emergency phone number;

Emergency phone number : 114 (Poison Control Center / For local calls only.)

2. Hazard identification;

2.1. Classification of substances and mixtures;

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

| | |
|--|------|
| Flammable Aerosol, Hazard Category 1 | H222 |
| Pressure Vessel | H229 |
| Eye irritation, Hazard Category 2 | H319 |
| BHOT Single Mrz, Hazard Category 3 (Dizziness) | H336 |

The full text of the H statements; see Section 16.

2.2. Label elements;

Classification of the mixture in accordance with Regulation (EC) No 1272/2008



Hazard Label (SEA) : ;
GHS02 GHS07

Warning word (SEA) : Danger

Hazard Statements (SEA) :

H222 - Highly flammable aerosol
H229 - Pressure vessel: May crack if heated.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.



SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

EUH066 - Repeated exposure may cause dryness and cracking of the skin.

Precautionary Statements (SEA) :

P210 Keep away from heat/sparks/flames/hot surfaces. - No smoking.

P211 - Do not spray towards flames or other sources of ignition.

P251 - Pressure vessel: Do not puncture or burn, even after use.

P261 - Avoid inhaling dust/fumes/gas/mist/vapors/spray.

P264 - Wash hands thoroughly with water after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 Use protective gloves/protective clothing/eye protection/face protection.

P312 - If you feel unwell, call the NATIONAL POISON CONTROL CENTER on 114 or your doctor/physician.

P304+P340 - IF INHALED: Remove the affected person to fresh air and ensure they are in a position where they can breathe easily.

P305+P351+P338 IF IN CONTACT WITH EYES: Rinse carefully with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Seek medical advice/attention.

P405 - Keep in a locked area.

P403+P233 - Store in a well-ventilated area. Keep container tightly closed.

P410+P403 - Protect from sunlight. Store in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122F.

P501: Dispose of contents/container in accordance with local/regional/national/international regulations (as specified). Indicate whether this applies to the contents, container, or both, as instructed by the manufacturer/supplier or competent authority.

2.3. Other damages;

It does not contain PBT or vPvB substances.

3. Information about its composition/ingredients;

3.1. Items;

Not applicable.

3.2. Mixtures

| Name of the Substance | CAS Number | EC Number | % | Classification in accordance with the "Regulation on the Classification, Labelling and Packaging of Substances and Mixtures" (SEA), published in the Official Gazette dated 11 December 2013 and numbered 28848 (mükerrer). | Pictograms |
|-----------------------|------------|-----------|------|--|-----------------------------|
| Acetone | 67-64-1 | 200-662-2 | 5-20 | Flame. Liquid 2, H225 Eye Test.2, H319 BHOT TEK MRZ.3,H336 EUH066 | GHS02 GHS07 Dangerous |
| Butanone | 78-93-3 | 201-159-0 | 5-20 | Flame. Liquid 2, H225 Eye Test.2, H319 BHOT TEK MRZ.3,H336 | GHS02 GHS07 Dangerous |



SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

| | | | | | |
|----------------|----------|-----------|-------|--|-----------------------------|
| Dimethyl ether | 115-10-6 | 204-065-8 | 50-70 | Flame Gas.1, H220 Liquefied Gas, H280 | GHS02 GHS04 Dangerous |
|----------------|----------|-----------|-------|--|-----------------------------|

The full text of the H statements: see Section 16

4. First aid measures;

4.1. Explanation of first aid measures;

| | |
|---------------------|--|
| General Information | Immediately remove contaminated clothing or footwear. Remove the victim from the scene. Flammable liquid and vapor. Ensure adequate ventilation. Seek medical assistance – show SDS or label if possible. If the victim is likely to lose consciousness, lay them on their side and transport them. |
| Inhalation | Remove the patient from the danger zone to fresh air and seek medical assistance. Keep the patient warm and allow them to rest. Administer oxygen if necessary. Perform cardiopulmonary resuscitation (CPR) if cardiac arrest occurs. |
| Skin contact | Remove all contaminated clothing and shoes. Wash the affected area with soap and water for 15 minutes. Apply cream to the skin. Seek medical attention if irritation occurs. |
| Eye contact | Immediately lift your eyelids and rinse thoroughly with plenty of water for 15 minutes. Remove contact lenses if possible. Continue rinsing. Seek medical attention if you experience pain, burning, or photophobia. |
| If swallowed | Do not induce vomiting. If vomiting occurs, keep the head low to prevent aspiration into the lungs. Rinse the mouth. Give water to drink. Do not give milk or alcohol. Do not give anything by mouth to an unconscious person. Take to the hospital immediately. Activated charcoal can be given to replace the acetone. |

4.2. Significant symptoms and effects, both immediate and delayed.

| | |
|--------------|--|
| Inhalation | : Airway irritation, sore throat, headache, nausea, cough, difficulty breathing, chest tightness, gasping for air. |
| Skin contact | : Skin irritation, dryness, and cracking. |
| Eye contact | : Eye irritation, redness, swelling. |
| If swallowed | : Causes stomach and intestinal upset. |

4.3. The first signs that require medical intervention and specialized treatment.

Treat symptomatically.

5. Firefighting measures;

5.1. Fire extinguishers

| | |
|--------------|--|
| Suitable for | : Carbon dioxide, dry chemicals, water mist, alcohol-resistant foam. |
| Not suitable | : Do not use a water jet. Using water with foam can damage the foam. |

5.2. Specific hazards arising from the substance or mixture.

| | |
|--|--|
| Specific exposure hazards | : Vapors accumulating on the surface due to carbon monoxide formation can cause burns. |
| Hazardous thermal decomposition products | : Carbon monoxide, carbon dioxide, and unburned hydrocarbons produced during combustion. |



SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

5.3. Recommendations for firefighting teams

Special for firefighters. Use full-face mask protective clothing in positive pressure mode with a breathing apparatus. Cool the outside of the containers with water.

6. Measures to prevent accidental release;

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid sources of ignition. Do not smoke. Avoid inhaling vapors. Ensure adequate ventilation. Vapors may accumulate in confined spaces. Use chemical protective clothing and a respirator.

6.2. Environmental measures

Environmental measures : Prevent spills and spread. Prevent spread into sewers, drains, rivers, lakes, and streams. If spillage occurs in enclosed areas, ensure adequate ventilation. If spillage occurs into water sources, notify the authorities.

Other information : Unknown.

6.3. Methods and materials for preservation and cleaning.

Cleaning methods : Vacuum up large debris. Absorb with inert absorbents (sand, soil, vermiculite, etc.). Send to waste collection areas. Ensure adequate ventilation. Avoid sources of flame and do not smoke.

6.4. References to other sections

References to other sections : See also section 8.

7. Handling and storage;

7.1. Precautions for safe handling

Precautions for safe handling : Handle in well-ventilated areas. Do not inhale vapors. Avoid skin contact. Prevent static electricity buildup. Prevent slippery surfaces. Wear personal protective equipment. Do not smoke. Do not eat or drink. Use a grounding system. Do not swallow. Use only explosion-proof equipment.

7.2. Conditions for secure storage, including disputes.

Storage conditions : Store in a way that will not contaminate water sources. Static electricity generation must be prevented. Store away from flames and heat sources. Store away from oxidizers and corrosive materials. Store in a cool, well-ventilated environment. Keep the packaging tightly closed. Opened packaging must be tightly resealed to prevent leakage. Vapors accumulating at the top may be explosive if not jacketed with inert gas. Avoid direct sunlight. Store between 5-25°C. Do not smoke.

Recommended packaging : Store only in the packaging in which it was supplied.

7.3. Specific end uses

Usage : Use only as directed.

8. Exposure control/personal protection;

8.1. Control parameters

Acetone

| Observed Effects | Exposure | DNEL | Type of Toxicity |
|------------------|----------|------|------------------|
|------------------|----------|------|------------------|

SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

| Worker damage limits | | | |
|---|---------------------------|------------------------------------|--|
| Inhalation - Systemic Effects | Prolonged exposure | 1210 mg/ m ³ | |
| | Acute/Short-term exposure | Low damage | |
| Inhalation - Local Effects | Prolonged exposure | Low damage | |
| | Acute/Short-term exposure | 2420 mg/ m ³ | |
| Dermal-Systemic Effects | Prolonged exposure | 186 mg/kg body weight/day | |
| | Acute/Short-term exposure | 8238 mg/kg body weight/day (NOAEL) | |
| Dermal-Local Effects | Prolonged exposure | Low damage | |
| | Acute/Short-term exposure | Low damage | |
| Eye-Local Effects | Low damage. | | |
| Damage limits for the general population. | | | |
| Inhalation - Systemic Effects | Prolonged exposure | 200 mg/ m ³ | |
| | Acute/Short-term exposure | Low damage | |
| Inhalation - Local Effects | Prolonged exposure | Low damage | |
| | Acute/Short-term exposure | Low damage | |
| Dermal-Systemic Effects | Prolonged exposure | 62 mg/kg body weight/day | |
| | Acute/Short-term exposure | Low damage | |
| Dermal-Local Effects | Prolonged exposure | Low damage | |
| | Acute/Short-term exposure | Low damage | |
| Oral-Systemic Effects | Prolonged exposure | 62 mg/kg body weight/day | |
| | Acute/Short-term exposure | Low damage | |
| Eye-Local Effects | Low damage. | | |

Butanone

| Observed Effects | Exposure | DNEL | Type of Toxicity |
|---|--------------------|----------------------------|------------------------|
| Worker damage limits | | | |
| Inhalation - Systemic Effects | Prolonged exposure | 600 mg/ m ³ | Repeated Dose Toxicity |
| Dermal-Systemic Effects | Prolonged exposure | 1161 mg/kg body weight/day | Repeated Dose Toxicity |
| Damage limits for the general population. | | | |
| Inhalation - Systemic Effects | Prolonged exposure | 106 mg/ m ³ | Repeated Dose Toxicity |

SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

| | | | |
|-------------------------|--------------------|---------------------------|------------------------|
| Dermal-Systemic Effects | Prolonged exposure | 412 mg/kg body weight/day | Repeated Dose Toxicity |
| Oral-Systemic Effects | Prolonged exposure | 31 mg/kg body weight/day | Repeated dose toxicity |

Dimethyl ether

| Observed Effects | Exposure | DNEL | Type of Toxicity |
|---|---------------------------|--|------------------------|
| Worker damage limits | | | |
| Inhalation - Systemic Effects | Prolonged exposure | 1894 mg/ m ³ NOAEC: 23671 mg/ m ³ | Repeated dose toxicity |
| | Acute/short-term exposure | Low damage | |
| Inhalation - Local Effects | Prolonged exposure | No damage was reported. | |
| | Acute/short-term exposure | No damage was reported. | |
| Dermal-Systemic Effects | Prolonged exposure | No damage was reported. | |
| | Acute/short-term exposure | No damage was reported. | |
| Dermal-Local Effects | Prolonged exposure | No damage was reported. | |
| | Acute/short-term exposure | No damage was reported. | |
| Eyes | | No damage was reported. | |
| Damage limits for the general population. | | | |
| Inhalation - Systemic Effects | Prolonged exposure | 471 mg/ m ³ NOAEC: 11777 mg/ m ³ | Repeated dose toxicity |
| | Acute/short-term exposure | Low damage | |
| Inhalation - Local Effects | Prolonged exposure | No damage was reported. | |
| | Acute/short-term exposure | No damage was reported. | |
| Dermal-Systemic Effects | Prolonged exposure | No damage was reported. | |
| | Acute/short-term exposure | No damage was reported. | |
| Dermal-Local Effects | Prolonged exposure | No damage was reported. | |
| | Acute/short-term exposure | No damage was reported. | |
| Oral-Systemic Effects | Prolonged exposure | No damage was reported. | |
| Oral-Systemic Effects | Acute/short-term exposure | No damage was reported. | |
| Eyes | | No damage was reported. | |

SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

8.2. Exposure controls

- Engineering measures : Ensure adequate general and local ventilation. The ventilation system should be regularly maintained and inspected. Observe the exposure limits of the product or content.
- Hygiene precautions : Do not eat, drink, or smoke while using the product. Wash your hands after handling.
- Personal protective equipment : The effectiveness of personal protective equipment depends, among other factors, on temperature and ventilation. Professional advice should be sought depending on the specific situation.
- Body protection : Wear protective clothing, work overalls or suit and similar footwear conforming to EN 365/367, specifically standard 345. Suitable material: nitrile. Insulation time: impermeable.
- Respiratory protection : Use a respiratory device. Test that the filter is new and that the device fits snugly to your face. The gas and filter cartridge must comply with EN 14387. Full face masks and replaceable filter cartridges must comply with EN 136. Half face masks and replaceable cartridges must comply with EN 140.
- Hand protection : Wear gloves conforming to EN 374 standard . Suitable material: nitrile. ± 0.5 mm penetration time: impermeable. Replace gloves as needed.
- Eye protection : Use tightly fitting, chemical-protective goggles or a face shield. If there is a risk of inhalation, use a full-face gas mask.

9. Physical and chemical properties;

9.1. Basic physical and chemical properties

- Physical Appearance : Aerosol
- Color : Transparent
- Scent : Characteristic
- Odor threshold : Unknown
- Flash Point (°C) (min) : Unknown
- Boiling Point (°C) (min) : Unknown
- Density (g/cm³) : 0.7-0.9
- Viscosity (KU) : 5-15
- Vapor Pressure : Unknown
- Vapor density : Unknown
- Solvability : Unknown

9.2. Other information

No further information available.

10. Stability and reactivity;

10.1. Reaction

Reactivity : There are no known harmful reactive effects.

10.2. Chemical stability

Stability : It is stable under normal conditions.

10.3. Possibility of harmful reactions

SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

Reactivity : The likelihood of a reaction occurring is high in the presence of oxidizing agents.

10.4. Situations to avoid

Conditions to avoid : Avoid sources of flame such as heat and sparks. Containers may explode or burn fiercely due to excessive pressure when heated. Static electricity buildup must be prevented.

10.5. Substances to avoid

Materials to avoid: Oxidizing agents.

10.6. Harmful decomposition products,

Hazardous decomposition products : Do not decompose if stored and used under appropriate conditions. Products that decompose thermally or are compressed may include: harmful gases and vapors.

11. Toxicological information;

11.1. Information about toxic effects

| Article | Toxicity Type | Toxicity Zone | Test Animal | Conclusion |
|----------------|-------------------------------------|----------------|------------------------------|---|
| Butanone | Acute | Oral | Rat/Female-Male | LD 50: 2054 mg/kg |
| | | Dermal | Rabbit/Male | LD 50: >10 ml/kg |
| | Irritation | Eyelash | Rabbit | There is |
| | Sensibility | Dermal | Guinea Pig/Female | None |
| | Repeat Dose | Breathing | Rat/Female-Male | NOAEC: 5041 ppm |
| | Genetic | | Mouse/Female-Male | None |
| | Developmental toxicity | Breathing | Rat | NOAEC: 1002 ppm |
| | Reproductive toxicity | Oral | Rat/Female-Male | NOAEL; 1644 mg/kg/day |
| Dimethyl ether | Acute | Breathing | Rat/Male | LC 50: 164,000 ppm |
| | Genetic | | Drosophila melanogaster/Male | None |
| | Carcinogenicity | Breathing | Rat/Male-Female | None |
| | Reproductive/Developmental toxicity | Teratogenicity | Rat | NOAEL: 40000 ppm |
| | | Breathing | Rat/Male-Female | None |
| Acetone | Acute | Oral | Rat | LD50: 5800 mg/kg |
| | | Breathing | Rat | LC50: 132000 mg/m ³ (3s) 76000 mg/m ³ (4s) |
| | Dermal | Guinea Pig | LD50: 7400 mg/kg | |

SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

| | | | | |
|------------------------|-------------|-----------|-------------------------------|--------------------------------|
| | Irritation | Dermal | | None |
| | | Eyelash | | There is |
| | Sensibility | Dermal | | None |
| | Repeat Dose | Oral | | NOAEL; 900 mg/kg/day |
| | | Breathing | | NOAEC: 22500 mg/m ³ |
| | Genetic | | - | None |
| Developmental toxicity | Breathing | Rat | NOAEC: 5300 mg/m ³ | |

12. Ecological information;

12.1. Toxicity

| PNEC Values | Dimethyl Ether | Butanone | Acetone |
|------------------------|----------------------------------|--------------------------|--------------------------------------|
| Fresh water | 0.155 mg/l 1,549 mg/l (batch) | 55.8 mg/l | 10.6 mg/l 21 mg/l (batch release) |
| Marine | 0.016 mg/l | 55.8 mg/l | 1.06 mg/l |
| STP | 160 mg/l | 709 mg/l | 100 mg/l |
| Sediment (Fresh water) | 0.681 mg/kg sediment dw | 284.74 mg/kg sediment dw | 30.4 mg/kg sediment dw |
| Sediment (Marine) | 0.069 mg/kg sediment dw | 284.7 mg/kg sediment dw | 3.04 mg/kg sediment dw |
| Soil | 0.045 mg/kg soil dw | 22.5 mg/kg soil dw | 29.5 mg/kg soil dw |
| Predators | - | 1000 mg/kg food | - |
| Weather | | | |

12.2. Persistence and degradability

Persistence : Biodegradable.

12.3. Bioaccumulation potential

Potential for bioaccumulation : There is no known potential for bioaccumulation.

12.4. Mobility in the soil

Mobility : Not applicable.

12.5. Results of PBT and vPvB assessment

PBT/vPvB values : Does not contain PBT or vPvB substances.

12.6. Other negative effects

Other information : Not applicable.

13. Disposal information;

13.1. Waste processing methods

Product residue : Recyclable container. Do not puncture or burn, even after use. Do not dispose of empty packaging with normal household waste. Containers should be recycled or reused. Product residues, including non-empty packaging, should be treated as chemical waste.

Additional warning : Unknown.

SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

European Waste Catalogue : Dispose of hazardous waste in an official chemical waste storage facility in accordance with Directive 91/689/EEC and under a waste law pursuant to Commission Decision 2000/532/EC.

Local regulations : Waste disposal must comply with applicable regional, national, and local laws and regulations. Local regulations may be stricter than regional and national requirements and must be complied with.

14. Transportation information;

14.1. UN Number : UN 1950

14.2. Appropriate UN shipping name

Suitable shipping name : AEROSOLS

Proper shipping name (IMDG, IATA) : AEROSOLS

14.3. Transportation hazard class(es) : 2 (ADR/RID/ADN/IMDG/IATA)

Classification Code : 5F (ADR/RID/ADN)

Hazard Label : 2.1



14.4. Packaging group : None

14.5. Environmental damage

Marine pollutant : No

14.6. Special measures for the user

Unless otherwise stated, measures applicable to safe transport will be taken.

IATA Cargo Aircraft: 203

IMDG - Technical name: Aerosol

IMDG Page: FD, SU

14.7. Public transport according to MARPOL 73/78 Annex II and IBC code.

Marpol : As per the instructions above, it is not a hazardous product.

15. Knowledge of legislation;

15.1. Specific safety, health and environmental regulations for the substance or mixture.

National Legislation

- Turkish Ministry of Environment and Urbanization, Regulation No. 28848, dated December 11, 2013, on the Classification, Labelling and Packaging of Substances and Mixtures.
- Turkish Ministry of Environment and Urbanization, Waste Management Regulation, dated April 2, 2015, numbered 29314.
- Turkish Ministry of Labour and Social Security, Regulation No. 28733 dated August 12, 2013, on Health and Safety Measures in Work with Chemical Substances.
- Turkish Ministry of Labour and Social Security, Regulation No. 28695 dated July 2, 2013, on the Use of Personal Protective Equipment in Workplaces.
- Turkish Ministry of Labour and Social Security, Occupational Health and Safety Law No. 6331, dated June 30, 2012.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

16. Other information;

Abbreviations



SAFETY DATA SHEET

PRE FILLED

Product Name: Pre Filled
GBF Form No: M-00155

Preparation Date: 10.12.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended.

Flammable Liquid 2 : Flammable Liquid, Hazard Category 2.
Eye Irritation 2 : Serious Eye Irritation, Hazard Category 2
BHOT TEK. MRZ 3 : Specific Target Organ Toxicity-Single Exposure, Category 3
Flammable Gas 1 : Flammable Gas, Hazard Category 1
LD50 : The dose of a substance that causes 50% (half) death in the test animal group (Median Lethal Dose)
LC 50 : Concentration of a substance causing 50% (half) mortality in a test animal group.
ADR : European Agreement concerning the international carriage of dangerous goods by road.
IMDG : International Maritime Dangerous Goods
IATA : International Air Transport Association
ADN : European Agreement concerning the international carriage of dangerous goods by inland waterways
RID : European Agreement concerning the international carriage of dangerous goods by rail.
Merpel 73/78 : International Convention for the Prevention of Pollution from Ships, 1973, as amended by Protocol 1978. IBC: International Code for the Construction and Equipment of Ships Carrying Dangerous Bulk Chemicals (International Bulk Chemicals Code)
WEL : Workplace Exposure Limit
TWA : Workplace Exposure Limits
STEL : Short-Term Exposure Limit
EC No : European Community Number
CAS : Service for Chemical Theories
PBT : Persistent, Bioaccumulative, and Toxic Substance.
vPvB : Very Persistent, Highly Bioaccumulative
DNEL : Derived Effect Unobserved Time
Certificate Number: TÜV/11.302.03
Certificate Expiration Date: 05.11.2030

LEGAL NOTICE (DISCLAIMER)

The evaluations contained in the Product Safety Data Sheet have been prepared based on the information currently available to us and are published for the purpose of identifying the products in terms of health, safety, and environmental aspects. Maxray Kimya San. ve Tic. Ltd. Şti. makes no representation or warranty, either express or implied, regarding the accuracy or completeness of the data contained herein. This document should not be interpreted as a guarantee of any specific property of the product. The data and recommendations provided are applicable only to cases in which this product is sold for the specified application(s). This product should not be used for any purpose other than the stated application area without consulting Maxray Kimya San. ve Tic. Ltd. Şti.