

SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray
GBF Form No: M-00092

Preparation Date: 23.11.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

1. Description of the substance/mixture and of the company/distributor;

1.1. The identity of the substance/mixture;

Product form : Mixture
Trade Name : Chain Lubrication Spray
EC Number : Unknown
CAS Number : Unknown

1.2. Identified uses of the substance or mixture and uses advised against;

It is used in chain and sliding mechanisms. It can also be used in working machinery. It is also suitable for chains used in motorcycles.

1.3. Information about the supplier of the Safety Data Sheet;

Manufacturer : MAXRAY Kimya San. Tic. Ltd. Şti.
Address : Mimar Sinan Mah. Üsküdar Cad. YEDPA No:1 Cad. Inner door No:2
ATAŞEHİR/İSTANBUL
Phone : +90 850 307 04 47
Email : info@maxray.com.tr
Contact Person : Nurullah Düzgün
Product Code : MX-77074
Product Type : Industrial

1.4. Emergency phone number;

Emergency phone number : 114 (Poison Control Center / For local calls only.)

2. Hazard identification;

2.1. Classification of substances and mixtures;

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

Flammable Aerosol, Hazard Category 1 H222
Pressured Container H229
Aspiration Toxicity, Hazard Category 1 H304

The full text of the H statements; see Section 16.

2.2. Label elements;

Classification of the mixture in accordance with Regulation (EC) No 1272/2008



Hazard Label (SEA) :

GHS02

GHS08

Warning word (SEA) : Danger

Hazard Statements (SEA) :

H222 - Highly flammable aerosol.

H229 – Pressured Container: May burst when heated.

H304 - Fatal if inhaled or swallowed.

Precautionary Statements (SEA) :

P102 - Keep out of reach of children.

P201 - Read the special instructions before use.

SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray
GBF Form No: M-00092

Preparation Date: 23.11.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

P202 - Do not handle unless all safety warnings have been read and understood.

P210 Keep away from heat/sparks/flames/hot surfaces. - No smoking.

P211 - Do not spray towards flames or other sources of ignition.

P251 - Pressure vessel: Do not puncture or burn, even after use.

P281 - Use personal protective equipment.

IF SWALLOWED: Contact a poison control center or doctor/physician.

If exposed to or interacting with P308+P313: Seek medical advice/care.

P331 - Do not induce vomiting.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122F.

P405 - Keep in a locked area.

P501: Dispose of contents/container in accordance with local/regional/national/international regulations (as specified). Indicate whether this applies to the contents, container, or both, as instructed by the manufacturer/supplier or competent authority.

2.3. Other damages;

It does not contain PBT or vPvB substances.

3. Information about its composition/ingredients;

3.1. Items;

Not applicable.

3.2. Mixtures

Name of the Substance	CAS Number	EC Number	%	Classification in accordance with the "Regulation on the Classification, Labelling and Packaging of Substances and Mixtures" (SEA), published in the Official Gazette dated December 11, 2013, and numbered 28848 (mükerrer).	Pictograms
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	918-481-9	50-60	Asp.Tok.1, H304 EUH066	GHS08 Dangerous
Lubricating oils	74869-22-0	278-012-2	10-20	Unclassified.	-
Petroleum gases, liquefied (<0.1% 1,3-butadiene)	68476-85-7	270-704-2	30-35	Flame. Gas 1, H220 Dissolved Gas, H280	GHS02 GHS04 GHS08 Dangerous

The full text of the H statements: see Section 16

4. First aid measures;

4.1. Explanation of first aid measures;

General Information

If any discomfort persists, seek medical attention. Ventilate the area. Immediately remove contaminated clothing or footwear.

SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray
GBF Form No: M-00092

Preparation Date: 23.11.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

Inhalation	Move the victim to fresh air. Loosen any tight clothing. Remove the patient from the danger zone and seek medical assistance. If the patient is unconscious, turn them to their side. Keep the patient warm and allow them to rest. Administer oxygen if breathing is difficult. Perform cardiopulmonary resuscitation (CPR) if cardiac arrest occurs. If H ₂ S or CO inhalation occurs, rescuers should wear breathing apparatus, a harness, and a safety rope, and follow emergency procedures. The victim should be immediately moved to fresh air. If breathing stops, perform artificial respiration. Obtain medical assistance.
Skin contact	Remove all contaminated clothing and footwear. Wash thoroughly before reuse. Wash well with plenty of soap and water for 15 minutes. Seek medical attention if redness or pain occurs.
Eye contact	Immediately rinse your eyes with plenty of water for 15 minutes, keeping your eyelids raised. Remove contact lenses if possible. Seek medical attention if discomfort persists.
If swallowed	Do not induce vomiting. Consult your doctor immediately. Lips and mouth may become numb. Do not give anything by mouth to an unconscious patient.

4.2. Significant symptoms and effects, both immediate and delayed.

Inhalation	: Inability to breathe.
Skin contact	: Unknown
Eye contact	: Unknown
If swallowed	: Unknown

4.3. The first signs that require medical intervention and specialized treatment.

Treat symptomatically.

5. Firefighting measures;

5.1. Fire extinguishers

Suitable for	: Carbon dioxide, dry chemicals, dry sand, fire extinguishing foam. For large fires: Water spray, water mist, or foam.
Not suitable	: Do not use a water jet.

5.2. Specific hazards arising from the substance or mixture.

Specific exposure hazards	: Unknown.
Hazardous thermal decomposition products	Carbon monoxide, carbon dioxide, smoke, and soot can be produced during combustion.

5.3. Recommendations for firefighting teams

Special for firefighters.	Use protective clothing, including a full-face mask and respiratory support. Cool the outside of containers with water. The product may produce vapors that can explode when mixed with air. It can cause sudden flames. Pouring it down the drain may also cause a fire or explosion.
---------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6. Measures to prevent accidental release;

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	: Avoid sources of ignition. Do not smoke. Wear protective clothing. Avoid inhaling vapors. Keep unnecessary people away. Prevent entry
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray
GBF Form No: M-00092

Preparation Date: 23.11.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

to and isolate the hazardous area. Review evacuation needs. Stop the flow if there is no risk. Absorb spills with absorbents. Extra precautions should be taken in case of H₂S or CO formation. Special protective clothing should be worn. Personnel should be trained.

6.2. Environmental measures

Environmental measures : Prevent spills and spread. Prevent contamination of sewers, drains, and groundwater. Report spills to the authorities if they pollute streams or sewers.

Other information : Unknown.

6.3. Methods and materials for preservation and cleaning.

Cleaning methods : Absorb small spills with a cloth or cotton ball. Take them to waste collection areas. Ensure adequate ventilation. Avoid sources of ignition and do not smoke. For large spills, use a ditch or collection basin and notify the authorities.

6.4. References to other sections

References to other sections : See also section 8.

7. Handling and storage;

7.1. Precautions for safe handling

Precautions for safe handling : Handle in well-ventilated areas. Prevent vapor formation. Do not smoke or eat in handling and storage areas. Handle away from sources of flame.

7.2. Conditions for secure storage, including disputes.

Storage conditions : Store away from flames and heat sources. Keep containers closed when not in use. Store in a dry, cool, well-ventilated place away from direct sunlight. Store in original packaging. Jacket with inert gas for safe handling.

Recommended packaging : Store only in the packaging in which it was supplied.

7.3. Specific end uses

Usage : Use only as directed.

8. Exposure control/personal protection;

8.1. Control parameters

Petroleum gases, liquefied (<0.1% 1,3-butadiene)

Observed Effects	Exposure	DNEL	Type of Toxicity
Worker damage limits			
Inhalation - Systemic Effects	Prolonged exposure	2.21 mg/ m ³	Carcinogenicity
Dermal-Systemic Effects	Prolonged exposure	23.4 mg/kg body weight/day	Carcinogenicity
Damage limits for the general population.			
Inhalation - Systemic Effects	Prolonged exposure	0.066 mg/ m ³	Carcinogenicity

SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray
GBF Form No: M-00092

Preparation Date: 23.11.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

Observed Effects	Exposure	DNEL	Type of Toxicity
Worker damage limits			
Inhalation - Systemic Effects	Prolonged exposure	2.7 mg/ m ³	
Inhalation - Local Effects	Prolonged exposure	5.6 mg/ m ³	
Dermal-Systemic Effects	Prolonged exposure	1 mg/kg body weight/day	Neurotoxicity
Damage limits for the general population.			
Oral-Systemic Effects	Prolonged exposure	0.74 mg/kg body weight/day	Acute toxicity

8.2. Exposure controls

- Engineering measures : Ensure adequate general and local ventilation. The ventilation system should be regularly maintained and inspected. Observe the exposure limits of the product or content.
- Hygiene precautions : General hygiene rules regarding the use of chemical substances should be applied. Wash your hands during breaks and after work. Keep away from food, drinks, and meals. Remove contaminated clothing and protective equipment before entering eating areas.
- Personal protective equipment : The effectiveness of personal protective equipment depends, among other factors, on temperature and ventilation. Professional advice should be sought depending on the specific situation.
- Body protection : Wear protective clothing, work overalls or suit and similar footwear conforming to EN 365/367, specifically standard 345. Suitable material: nitrile. Insulation time: impermeable.
- Respiratory protection : In well-ventilated areas, no special equipment is required. In poorly ventilated areas, use artificial respiration.
- Hand protection : Wear gloves conforming to EN 374 standard . Suitable material: nitrile. ± 0.5 mm penetration time: impermeable. Replace gloves as needed.
- Eye protection : Use tightly fitting, chemical-protective goggles or a face shield. If there is a risk of inhalation, use a full-face gas mask.

9. Physical and chemical properties;

9.1. Basic physical and chemical properties

- Physical Appearance : Aerosol
Color : Yellow
Scent : Characteristic
Odor threshold : Unknown
Flash Point (°C) (min) : Unknown
Boiling Point (°C) (min) : Unknown
Freezing Point (°C) : Unknown
Density (g/ cm³) : 0.80-0.85
pH : Unknown
Viscosity (mPa.s) : 2-7
Vapor Pressure (20°C) : Unknown

SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray
 GBF Form No: M-00092

Preparation Date: 23.11.2025
 Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

Vapor density : Unknown

9.2. Other information

No further information available.

10. Stability and reactivity;

10.1. Reaction

Reactivity : There are no known harmful reactive effects.

10.2. Chemical stability

Stability : It is stable under normal conditions.

10.3. Possibility of harmful reactions

Reactivity : The likelihood of a reaction occurring is high in the presence of oxidizing agents.

10.4. Situations to avoid

Conditions to avoid : Avoid sources of flame such as heat and sparks.

10.5. Substances to avoid

Materials to avoid: Oxidizing agents.

10.6. Harmful decomposition products,

Hazardous decomposition products : Do not decompose if stored and used under appropriate conditions. Products that decompose thermally or are compressed may include: harmful gases and vapors.

11. Toxicological information;

11.1. Information about toxic effects

Article	Toxicity Type	Toxicity Zone	Test Animal	Conclusion
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Acute	Oral	Rat	LD 50 > 5000 mg/kg
		Breathing	-	LC 50 > 5000 mg/ m ³
		Dermal	Rabbit	LD 50 > 5000 mg/kg
	Irritation	Dermal	Rabbit	There is
		Sensibility	Dermal	-
	Repeat Dose	Oral	Rat	NOAEL >5000 mg/kg
		Breathing	Rat	NOAEL > 10400 mg/ m ³
	Genetic		-	None
Reproductive toxicity	Breathing	Rat / Female-Male	NOAEC; ≥400 ppm	
Developmental toxicity	Oral	Rat	NOAEL; 500 mg/kg/day	
Lubricating oil	Acute	Oral	-	LD50: 5000 mg/kg
		Breathing	-	LC 50: 5000 mg/ m ³
		Dermal	-	LD50: 2000 mg/kg
	Irritation	Dermal	-	None
		Eyelash	-	None
	Sensibility	Dermal	-	None
	Repeat Dose	Oral	Rat	LOAEL; 125 mg/kg/day
		Inhalation/Systemic	Rat	NOAEC; 980 mg/ m ³

SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray
 GBF Form No: M-00092

Preparation Date: 23.11.2025
 Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

		Dermal	Mouse	LOAEL; 100 mg/kg/day
	Genetic			None
	Carcinogenicity	Dermal	Mouse	Chronic
	Reproductive/Developmental toxicity	Oral	Rat	NOAEL; 1000 mg/kg/day
Dermal		Rat	NOAEL; 1000 mg/kg/day	
Petroleum gases, liquefied (<0.1% 1,3-butadiene)	Acute	Breathing	Rat/Female-male	LC 50: 800,000 ppm EC 50: 280000 ppm
	Repeat Dose	Inhalation/Systemic	Rat/Female-Male	No harmful effects have been observed. NOAEC; 19678 mg/m ³
	Genetic			None
	Reproductive		Rat/Female-Male	NOAEC: 16000 ppm
	Teratogenicity	Breathing	Rat	NOAEC: 16000 ppm
	Carcinogenicity		Rat/Female-Male	NOAEC: 10000 ppm An effect was observed at 17200 mg/m ³

12. Ecological information;

12.1. Toxicity

	Petroleum gases, liquefied (<0.1% 1,3-butadiene)
Short-term toxicity (fish)	LC50: 49.47 mg/l (96 hours)
Long-term toxicity (fish)	
Short-term toxicity (invertebrates)	LC50: 69.43 mg/l (48 hours)
Long-term toxicity (invertebrates)	
Toxicity (Algae, cyanobacteria)	EC50: 12.32 mg/l (96 hours)
Toxicity (Microorganisms)	EL50: 51.6 mg/l (48 hours)

PNEC Values	Lubricating oil
Fresh water	-
Marine	-
STP	-
Sediment (Fresh water)	-
Sediment (Marine)	-
Soil	-
Predators	9.33 mg/kg food

Persistence and degradability

Persistence : Biodegradable.

12.2. Bioaccumulation potential

Potential for bioaccumulation : There is no known potential for bioaccumulation.

SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray Preparation Date: 23.11.2025
GBF Form No: M-00092 Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

12.3. Mobility in the soil

Mobility : Not applicable.

12.4. Results of PBT and vPvB assessment

PBT/vPvB values : Does not contain PBT or vPvB substances.

12.5. Other negative effects

Other information : Not applicable.

13. Disposal information;

13.1. Waste processing methods

Product residue : Recyclable container. Do not puncture or burn, even after use. Do not dispose of empty packaging with normal household waste. Containers should be recycled or reused. Product residues, including non-empty packaging, should be treated as chemical waste.

Additional warning : Unknown.

European Waste Catalogue : Dispose of hazardous waste in an official chemical waste storage facility in accordance with Directive 91/689/EEC and under a waste law pursuant to Commission Decision 2000/532/EC.

Local regulations : Waste disposal must comply with applicable regional, national, and local laws and regulations. Local regulations may be stricter than regional and national requirements and must be complied with.

14. Transportation information;

14.1. UN Number : UN 1950

14.2. Appropriate UN shipping name

Suitable shipping name : AEROSOLS

Proper shipping name (IMDG, IATA) : AEROSOLS

14.3. Transportation hazard class(es) : 2 (ADR/RID/ADN/IMDG/IATA)

Classification Code : 5F (ADR/RID/ADN)

Hazard Label : 2.1



14.4. Packaging group : None

14.5. Environmental damage

Marine pollutant : No

14.6. Special measures for the user

Unless otherwise stated, measures applicable to safe transport will be taken.

IATA Cargo Aircraft: 203

IMDG - Technical name: Aerosol

IMDG Page: FD, SU

14.7. Public transport according to MARPOL 73/78 Annex II and IBC code.

Marpol : As per the instructions above, it is not a hazardous product.



SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray
GBF Form No: M-00092

Preparation Date: 23.11.2025
Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

15. Knowledge of legislation;

15.1. Specific safety, health and environmental regulations for the substance or mixture.

National Legislation

- Turkish Ministry of Environment and Urbanization, Regulation No. 28848, dated December 11, 2013, on the Classification, Labelling and Packaging of Substances and Mixtures.
- Turkish Ministry of Environment and Urbanization, Waste Management Regulation, dated April 2, 2015, numbered 29314.
- Turkish Ministry of Labour and Social Security, Regulation No. 28733 dated August 12, 2013, on Health and Safety Measures in Work with Chemical Substances.
- Turkish Ministry of Labour and Social Security, Regulation No. 28695 dated July 2, 2013, on the Use of Personal Protective Equipment in Workplaces.
- Turkish Ministry of Labour and Social Security, Occupational Health and Safety Law No. 6331, dated June 30, 2012.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

16. Other information;

Abbreviations

Reproductive	System Toxic, Hazard Category 1A
Flammable Liquid 2	: Flammable Liquid, Hazard Category 2.
Aspiration	Toxicity, Hazard Category 1
LD50	: The dose of a substance that causes 50% (half) death in the test animal group (Median Lethal Dose)
LC 50	: Concentration of a substance causing 50% (half) mortality in a test animal group.
ADR	: European Agreement concerning the international carriage of dangerous goods by road.
IMDG	: International Maritime Dangerous Goods
IATA	: International Air Transport Association
ADN	: European Agreement concerning the international carriage of dangerous goods by inland waterways
RID	: European Agreement concerning the international carriage of dangerous goods by rail.
Merpol 73/78	: International Convention for the Prevention of Pollution from Ships, 1973, as amended by Protocol 1978. IBC: International Code for the Construction and Equipment of Ships Carrying Dangerous Bulk Chemicals (International Bulk Chemicals Code)
WEL	: Workplace Exposure Limit
TWA	: Workplace Exposure Limits
STEL	: Short-Term Exposure Limit
EC No	: European Community Number
CAS	: Service for Chemical Theories



SAFETY DATA SHEET

CHAIN LUBRICANT SPRAY

Product Name: Chain Lubricant Spray

Preparation Date: 23.11.2025

GBF Form No: M-00092

Revision Date/Number: 00/00

According to Commission Regulation (EU) 2020/878 as amended

PBT : Persistent, Bioaccumulative, and Toxic Substance.

vPvB : Very Persistent, Highly Bioaccumulative

DNEL : Derived Effect Unobserved Time

Va : Body weight

Certificate Number: TÜV/11.302.03

Certificate Expiration Date: 05.11.2030

LEGAL NOTICE (DISCLAIMER)

The evaluations contained in the Product Safety Data Sheet have been prepared based on the information currently available to us and are published for the purpose of identifying the products in terms of health, safety, and environmental aspects. Maxray Kimya San. ve Tic. Ltd. Şti. makes no representation or warranty, either express or implied, regarding the accuracy or completeness of the data contained herein. This document should not be interpreted as a guarantee of any specific property of the product. The data and recommendations provided are applicable only to cases in which this product is sold for the specified application(s). This product should not be used for any purpose other than the stated application area without consulting Maxray Kimya San. ve Tic. Ltd. Şti.